

White paper

June 2008

W580i and W580c



Sony Ericsson

Preface

Purpose of this document

This White Paper will be published in several revisions as the phone is developed. Therefore, some of the headings and tables below contain limited information. Additional information and facts will be forthcoming in later revisions.

The aim of this White Paper is to give the reader an understanding of technology and its main applications, as well as the main functions and features of the phone.

Note: This document contains general descriptions for this specific Sony Ericsson mobile phone.

People who can benefit from this document include:

- Operators
- Service providers
- Software developers
- Support engineers
- Application developers

This White paper is published by:

Sony Ericsson Mobile Communications AB,
SE-221 88 Lund, Sweden

Phone: +46 46 19 40 00

Fax: +46 46 19 41 00

www.sonyericsson.com/

© Sony Ericsson Mobile Communications AB,
2006. All rights reserved. You are hereby granted
a license to download and/or print a copy of this
document.

Any rights not expressly granted herein are
reserved.

First edition (June 2008)

Publication number: EN/LZT 108 9307 R8A

This document is published by Sony Ericsson Mobile Communications AB, without any warranty*. Improvements and changes to this text necessitated by typographical errors, inaccuracies of current information or improvements to programs and/or equipment, may be made by Sony Ericsson Mobile Communications AB at any time and without notice. Such changes will, however, be incorporated into new editions of this document. Printed versions are to be regarded as temporary reference copies only.

*All implied warranties, including without limitation the implied warranties of merchantability or fitness for a particular purpose, are excluded. In no event shall Sony Ericsson or its licensors be liable for incidental or consequential damages of any nature, including but not limited to lost profits or commercial loss, arising out of the use of the information in this document.

Sony Ericsson Developer World

On www.SonyEricsson.com/developer, developers will find documentation and tools such as phone White Papers, Developers Guidelines for different technologies, SDKs and relevant APIs. The Web site also contains discussion forums monitored by the Sony Ericsson Developer Support team, an extensive Knowledge Base, Tips & Tricks, example code and news.

Sony Ericsson also offers technical support services to professional developers. For more information about these professional services, visit the Sony Ericsson Developer World Web site.

Document history

| Change history | | |
|-------------------|-------------|-----------------------------|
| 26 March 2007 | Version R1A | Initial Release. |
| 12 April 2007 | Version R2A | Updated with feedback. |
| 5 June 2007 | Version R3A | Updated with feedback. |
| 10 July 2007 | Version R4A | Updated. |
| 24 July 2007 | Version R5A | Updated. |
| 9 August 2007 | Version R6A | Updated with model numbers. |
| 17 September 2007 | Version R7A | Updated with comments |
| 5 June 2008 | Version R8A | Updated with comments |

Contents

Product overview 5
 Key features 6
 Images 8

Technologies in detail 12

Facts and figures 25
 Abbreviations 53
 Related information 57

Product overview

Impress friends and colleagues with the sleek design of the W580. The design features a slim slider for your senses with inviting tactile surfaces that makes you want to touch and hold it. The built-in Walkman™, combines with the 512 MB Expandable Memory Stick Micro™ (M2™) to make the W580 a portable music device, as well as a phone.

W580 also has an impressive 2MP camera with 4x digital zoom and 1600 x 1200 resolution. Enjoy viewing pictures or video clips on the 2.0 inch, 240 x 320 pixel, 262k display. This phone supports EDGE Class 10 (Enhanced Data rates for Global Evolution) and GPRS (General Packet Radio Service) quad band 850/900/1800/1900 (Class 10 meaning 4+2 sum 5), and GSM (Global System for Mobile Communications). In addition to packet switched (PS) data, it also supports voice and circuit switched (CS) data.

The W580 is the ultimate mobile phone for the sports-minded and active individual. The design and sports functionality make W580 trendy, yet functional. Track your progress and expand your limits with the sports application. Record how your body performs during exercise and record graphical data that you can easily transfer to your PC.

Note: To be able to give updated information about the implemented technology and functionality of this product as soon as possible, this White Paper will be released in updated revisions.

Key features

2.0 inch color screen

The 2.0 inch (240 x 320 pixels) full graphic 262k color screen enhances viewing, facilitating high-quality multimedia and entertainment.

2.0 Megapixel camera

With the 2.0 Megapixel, fixed focus camera, taking pictures becomes easy and fun. The camera includes a 4x digital zoom and many user friendly features. The user interface adds extra quality when it comes to handling the camera.

Walkman™ player

The Walkman™ 2.0 player converts the phone into a portable MP3, MPEG4, H263 player. Play music and video clips, streamed or downloaded. The folder system enables you, for example, to organize your favorite songs into groups and create simple playlists.

TrackID™

Obtain title, artist and album information about songs when listening to the FM radio or by recording music from an external source using the microphone. TrackID™ is powered by Gracenote Mobile MusicID™.

Shake control

Press and hold the Walkman™ key, then shake your phone to pick and play a song in the album or playlist you are listening to – at random.

Communicorder

By using the built-in communicorder, a video recording can be captured and stored in the phone. A video clip can easily be sent off in a picture message for example to friends or family to share experiences with instantly. The W580 supports viewing video clips in full screen mode.

Gaming

Gaming is already a very popular feature in mobile phones, and with Advanced Java, users can add new games and skill levels to further enhance the entertainment value of Sony Ericsson phones. Several embedded games are included in the phone at purchase. Both 2D and 3D gaming is supported.

JAVA™

Download extra content with Java™, for example, new information- and entertainment-based applications. This gives users a chance to personalize the functions and features in their phones, and developers the opportunity to create new applications.

HTML web browser support

Browse the internet and look at the web sites in different ways with Access NetFront 3.3, an HTML browser which supports a complete web standard suite.

Disc2Phone

You can create your own playlists and albums and transfer them to the phone. Music files can be transferred from a computer to the phone memory, in a user-friendly way. Search for and select music on your

computer or audio CDs and convert your existing audio tracks to MP3 format. Disc2Phone will be included on the CD in the box.

RDS FM Radio

The FM radio with RDS (radio data system) offers instant and easy access to FM radio channels. The RDS function brings information directly to the screen, which is sent out by the currently tuned in radio station. Just plug in the handsfree that works as an antenna and start listening to desired music. The radio can also be used as an alarm signal.

Polyphonic Ringtones

With this format, the user can play, compose, edit and send melodies by using the Music DJ. The built-in sound synthesizer uses wave tables, real instrument sounds with 72 voices polyphonics. The new composer has an improved graphical user interface to simplify melody handling. All new and edited melodies are stored in MIDI format.

Bluetooth™ wireless technology

Several devices (simultaneous Bluetooth connections) can be connected to W580 using Bluetooth wireless technology up to 33 feet (10 meters) away. For example, the phone can be answered with a Bluetooth headset when it rings and images can be sent to another phone at the same time. Several mobile phones can take part in a Bluetooth supported game and the phone and a computer can exchange data such as images, video clips, business e-cards, music files and calendar data.

Personal Information Management (PIM)

Stay up to date with everyday events by synchronizing phone contacts, calendar appointments and tasks in the phone with similar programs in a computer. Synchronize via USB or Bluetooth using software provided on CD in the box (also available at www.SonyEricsson.com/support).

Memory Stick Micro™ (M2™)

The W580 supports Memory Stick Micro™ (M2™). Store up to 512 MB of content (pictures, audio, video clips etc.) on the included Memory Stick™. Additional memory sticks may be purchased separately. The W580 accommodates Memory Stick Micro™ (M2™) up to 4 GB. Transfer content to other Sony Memory Stick-compatible consumer products using an adapter, for example Sony digital cameras, camcorders, portable music players, TVs, photo printers and computers.

Mobile blogging

Share pictures with friends and family by sending them via the Internet to your personal blog.

Images









Technologies in detail

This chapter offers a detailed description of the technologies available in this product.

Functions and features

The following table is a complete description of the features in W580. It also compares the product with one other Sony Ericsson product.

| Feature | W580 | W710 | W850 |
|--|-------------------------------|-------------------------------|-------------------------------|
| 3D games support | Yes | Yes | Yes |
| Alarm clock Set a time and the phone will ring at that time. | Yes | Yes | Yes |
| AMR Adaptive MultiRate audio format for speech sounds. | Yes | Yes | Yes |
| Backlight Colored backlight to illuminate the phone screen. | White | White | White |
| Battery | 3.6V, 930mAh, Lithium Polymer | 3.6V, 900mAh, Lithium Polymer | 3.6V, 900mAh, Lithium Polymer |
| Battery charging time At least 90% charged after 120 minutes. | Yes | Yes | Yes |
| Bluetooth™ wireless technology Wireless connectivity between devices. Range - up to 33 feet (10 meters). | Version 2.0 | Version 2.0 | Yes |
| Business card exchange Exchange contact information. | Yes | Yes | Yes |
| Calculator | Yes | Yes | Yes |
| Calendar Fully functional calendar with day, week and month views and reminders. | Yes | Yes | Yes |
| Call list View calls made and calls received. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|--|--|---|---|
| Calorie counter Measures the calories used while walking or running. | Yes | Yes | No |
| Camera 2.0 Megapixel Fixed | 2.0 Megapixel Fixed | 2.0 Megapixel Fixed | 2.0 Megapixel Fixed |
| Camera button One press camera activation. | Yes | Yes | Yes |
| cHTML A mobile device adapted version of the standard Internet communications protocol HTML. | Yes | Yes | Yes |
| Clock Onscreen clock. | Yes | Yes | Yes |
| Co-branding area 7.02 x 28.36 mm | 7.02 x 28.36 mm | 6.86 x 21.82 mm | 6.51 x 21.8 mm |
| Code memo A secure place to store all PIN codes and other information. To access Code memo, only one PIN code is needed. | Yes | Yes | Yes |
| Color Style White Urban Grey Boulevard Black Metro Pink | Style White Urban Grey Boulevard Black Metro Pink | Performance Graphite Hatha Purple | Precious Black Golden White |
| Contacts Phonebook with fields for name, phone and fax numbers, email address, web address, title, company address info, personal address info and birthday. | Up to 1,000 contacts. Up to 2,500 phone numbers. | Up to 1,000 contacts. Up to 2,500 phone numbers. | Up to 1,000 contacts. Up to 2,500 phone numbers. |
| Conference calls Support for multi-party calling. | Yes | Yes | Yes |
| Content online Downloadable pictures, games, themes, ringtones available online. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|--|---|---|---|
| Copyright protection - DRM DRM (Digital Rights Management) features the rights and copy protection of downloaded content (audio, pictures, music tones, video, entertainment features such as games, java applications etc.). | Version 2.0 | Version 2.0 | |
| Design | Slider | Clamshell | Slider |
| Device Management (DM) DM utilizes GPRS as bearer (basic network connectivity needs to be in place) of the provisioning data and allows the operator to access the phone and check and set different settings such as Network connectivity (GPRS), email, MMS, WAP and JAVA. Device Management is achieved by supporting Over The Air provisioning 7.1 (OTA), OMA Client Provisioning 1.1 (CP) and OMA Device Management (DM) 1.2. | Yes | Yes | Yes |
| Digital zoom | 4x | 4x | 2.5x for pictures 4x for video clips 2x for video calls |
| Display Main Screen Type: Size: Resolution: Technology: Colors displayed together: Backlight color: Pixel ratio: | Full graphical 2.0 inches 240 x 320 pixels TFT 262K White 1.0 | Full graphical 1.9 inches 176 x 220 pixels TFT 262K White 1.0 | Full graphical 2.0 240x320 pixels TFT,QVGA 262K White 1.0 |

| Feature | W580 | W710 | W850 |
|--|-------------------------|--|-------------------------|
| External Display Type: Size: Resolution: Technology: Colors displayed together: Backlight color: | n/a | Full graphical 1.5 inches 128 x 128 pixels Grayscale 4-level Orange on black background. Display setting can change to invert when backlight turns off for improved readability. | n/a |
| EDGE EDGE provides all the benefits of GPRS at significantly higher data rates and enables feature-rich services that require higher data rates than GPRS can deliver. The added bandwidth can also be used to increase capacity for additional customers. W580 supports EDGE Class 10 (4 +2 - sum 5). | Yes | Yes | No |
| E-mail Built-in email client (POP3/IMAP4) with inbox, outbox, compose, send and other functions. Supports attachments. | Yes | Yes | Yes |
| EMS (Enhanced Messaging) Text messaging (SMS) with pictures and sounds. | Yes | Yes | Yes |
| Exterior description Length x Width X Thickness Weight | 99 x 47 x 14 mm 94 g | 88 x 48 x 24.5 mm 100 g | 98 x 47 x 21 mm 118g |
| Fast port A system connector which enables faster data transfer from phone to computer and computer to phone. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|--|---|---|---|
| File manager Folder structure storage to help store and organize pictures, sounds and other phone content. | Yes | Yes | Yes |
| FM radio with RDS (radio data support) FM radio with presets, auto and manual search. Portable handsfree is used as an antenna. | Yes | Yes | Yes |
| Games embedded | Yes | Yes | Yes |
| GPRS General Packet Radio Services - a communications standard enabling packet data transfer similar to Internet - 28.8 kbps - 58.6 kbps. It is recommended to have GPRS to use MMS and content download services. | Yes | Yes | Yes |
| High Speed Data HSCSD - a communications standard enabling GSM data transfer 14.4 kbps. | Yes | Yes | Yes |
| Icon Desktop 12 A graphic icon desktop with 12 interactive icons. | Yes | Yes | Yes |
| Infrared | No | Yes | Yes |
| Instant messaging (Wireless Village) A chat and presence service. See your friends' online status and mood. Invite them to group chats or have one-to-one conversations with them. | Yes | Yes | Yes |
| Java™ Support for Java™ technology. | Java 2, Micro Edition (J2ME™), Java 3D™ | Java 2, Micro Edition (J2ME™), Java 3D™ | Java Platform, Micro Edition™, Java 3D™ |

| Feature | W580 | W710 | W850 |
|---|---|---|--|
| Keys - navigation and more | 4+1 way navigation 2 selection Back Clear Walkman® key Activity menu Dedicated on/off key Side volume keys | Inside clamshell: 4+1 way navigation 2 selection keys Back Clear Walkman® key Internet/Operator Dedicated on/off key Camera key Volume keys On clamshell: play/ pause, skip forward, skip backward and menu. | 8 + 1 navigation 2 selection Back Clear Walkman® key Internet/Operator Activity Menu |
| Keys - keypad | 12 number keys | 12 number keys | 12 number keys |
| Memory, built-in Phone memory that is free to use (depending on software configuration/file content). Many applications share phone memory. The maximum amount of storage available for any one application, such as calendar entries, is affected by the amount of memory used by other applications, such as messaging, music, pictures, and so on. | Up to 12 MB | Up to 10 MB built-in | Up to 16 MB |
| Memory card slot A mini peripheral storage device capable of storing pictures, music, applications and more. Compatible with cameras, PCs and other devices. | Memory Stick Micro™ (M2™) support | Memory Stick Micro™ (M2™) support | Memory Stick PRO Duo™ support |
| Menu shortcuts A function making it possible to dedicate shortcuts to the most-used phone functions. | Yes | Yes | Yes |
| Mobile blogging Share pictures over the Internet on your personal Web page | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|---|---|---|--|
| MMS (Multimedia messaging) Picture messaging with text and sound. | Yes | Yes | Yes |
| MMS video Support in the phone for sending video using MMS. | Yes | Yes | Yes |
| Modem GSM Internet dial-up support. | Yes | Yes | Yes |
| Music mode All radio transmitters and receivers are deactivated, making it possible to use the phone only as a Walkman™ in airplanes, hospitals and other situations where using a mobile phone is not allowed. | Yes | Yes | Yes |
| Music tones Music tones, also called master tones, are DRM (Digital Rights Management) protected music by original artists. Various digital audio formats are supported. | Yes | Yes | Yes |
| MusicDJ™ A sampler music tool with MIDI drum, guitar, keyboard, bass and brass loops in different music styles, which can be combined to create polyphonic ringtones. | Yes | Yes | Yes |
| Networks | <ul style="list-style-type: none"> • GSM 850 • GSM 900 including e-GSM • GSM 1800 • GSM 1900 • GPRS • EDGE. | <ul style="list-style-type: none"> • GSM 850 • GSM 900 including e-GSM • GSM 1800 • GSM 1900 • GPRS • EDGE. | <ul style="list-style-type: none"> • UMTS 2100 • GSM 900 including e-GSM • GSM 1800 • GSM 1900 |
| OTA settings WAP, e-mail and other settings can be sent Over-The-Air to the phone. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|--|------|------|------|
| Pedometer Calculate the distance walked using the built-in pedometer. | Yes | Yes | No |
| PhotoDJ™ A drawing tool in the phone where new pictures can be drawn from scratch or by altering existing ones. | Yes | Yes | Yes |
| Pictbridge Print camera album pictures via the USB cable connected to a PictBridge™ compatible printer. | Yes | Yes | Yes |
| Picture gallery A thumbnail image gallery where sections of several pictures can be seen in the screen at the same time. | Yes | Yes | Yes |
| Picture phonebook Add pictures to the contacts. When someone calls, a picture of that person appears on screen. | Yes | Yes | Yes |
| PlayNow™ Download and pre-listen to music ringtones straight from the phone desktop in three clicks. | Yes | Yes | Yes |
| PlayNow™ Games Preview games straight from the phone desktop in three clicks before you purchase and download. | Yes | Yes | Yes |
| Polyphonic ringtones | 72 | 72 | 40 |
| Predictive text input | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|--|------|------|------|
| QuickShare™ QuickShare™ is easy experience sharing. With an integrated camera a view can be captured and sent in seconds. | Yes | Yes | |
| Shake control Press and hold the Walkman™ key, then shake your phone to pick and play a song in the album or playlist you are listening to – at random. | Yes | No | No |
| SIM card lock The possibility to protect the SIM card with a four-digit PIN code. | Yes | Yes | Yes |
| SMS long (Text Messaging) Concatenated SMS text messaging. | Yes | Yes | Yes |
| Sony Ericsson Remote Update Service Download the latest operator approved version of the mobile phone software over the air. | Yes | Yes | Yes |
| Sony Ericsson Update Service Connect the phone to an Internet - connected computer, download the latest operator-approved version of the mobile device software from the web, www.SonyEricsson.com/support and update the mobile device. | Yes | Yes | Yes |
| Sound recorder A mini recording device in the phone that can record voice messages or other sounds. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|--|---|---|--|
| Speakerphone Loudspeaker suitable for using the phone as an office handsfree. | Yes | Yes | Yes |
| Speed dialing Allocate contacts in the phonebook to specific keys on the keypad. | Yes | Yes | Yes |
| Standby Time <ul style="list-style-type: none"> • Listening to MP3s in Flight mode • With FM radio on in Phone mode • Listening to MP3s in Phone mode | Up to 370 hours Up to 20 hours Up to 25 hours Up to 20 hours | Up to 370 hours Up to 17 hours Up to 25 hours Up to 16.5 hours | Up to 350 hours Information not available |
| Status view The screen shows the network being used, time and other status information. | Yes | Yes | Yes |
| Stopwatch | Yes | Yes | Yes |
| SVG Tiny Scalable Vector Graphics for impressive animated wallpapers, menus and other graphic elements. | 1.2 | 1.2 | 1.1 |
| Synchronization PC Synchronize and share phone content with PC. | Yes | Yes | Yes |
| Talk Time | Up to 9 hours | Up to 9 hours | Up to 9 hours |
| Tasks Keeps track of important things to do. | Yes | Yes | Yes |
| Themes display Phone menu texts and background graphics. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|---|-------------------|------|------|
| Timer Set the phone to alert after a specific time lapse. | Yes | Yes | Yes |
| TrackID™ TrackID™ is a free music recognition service powered by Gracenote Mobile MusicID™. Use the feature to search for title, artist and album names about a song. | Yes | Yes | Yes |
| Training Manager Software View recorded data and transfer to your PC. | Yes | Yes | No |
| USB connectivity support Connect the phone to a computer with a USB cable and the memory in the phone appears on the computer screen as a mass storage device. | 2.0, Full version | Yes | Yes |
| Vibrating alert The phone vibrates when a call comes in. | Yes | Yes | Yes |
| Video player Record, play and transfer video clips to another phone or a computer via available transfer method. | Yes | Yes | Yes |
| Video streaming Real time streaming of video, for example, live cam. Media can also be downloaded and saved in the phone memory and then used with the Walkman™ player. | Yes | Yes | Yes |
| VideoDJ™ Create video sequences by combining different clips and adding music and images. | Yes | Yes | Yes |

| Feature | W580 | W710 | W850 |
|---|-------------|-------------|-------------|
| Viewfinder screen When using an in-phone camera or snap-on accessory camera, the picture can be previewed before it is captured. | Yes | Yes | Yes |
| Voice control Voice answer, reject and call. Assign voice commands to items in the phonebook and when a call is made, the voice command can be used instead of pressing keys. | Yes | Yes | Yes |
| Voicemail Support for voice mail operator service including automatic answering and message recording. | Yes | Yes | Yes |
| Walkman™ player Advanced digital music player. Supports playing music or video clips, streamed or downloaded. | Version 2.0 | Version 1.4 | Version 2.0 |
| WAP 2.0 XHTML A mobile Internet standard to access specially designed Internet sites. WAP 2.0 supports color and interactive lists. | Yes | Yes | Yes |

Facts and figures

This chapter offers readers a detailed listing of all the technical data relating to the product. Comprehensive descriptions of performance and technical characteristics are presented in table format for quick and easy access.

Technical specifications

General technical data

| | |
|--------------------------------|---|
| System | Quad-band GSM phase 2 recommendations. GSM850 (3GPP 31.101-1), GSM 900 (CTR 19 and CTR 20), GSM 1800 (CTR 31 and CTR 32), GSM 1900 and e-GSM mode supported. (GSM 900 not available on W712a) |
| Speech coding | HR, FR, EFR, and AMR, for high speech quality. |
| GSM SIM/ USIM card | GSM SIM - GSM 11.11, Small plug-in card, 1,8 V and 3 V. |
| Memory, built-in (user free) | 12 MB built-in memory (depending on software configuration/file content) |
| Memory, expandable memory card | <ul style="list-style-type: none"> • 512 MB Expandable Memory Stick Micro™ included. • Up to 4GB on Expandable Memory Stick Micro™ (M2™), sold separately. |

Performance and technical characteristics

| Dimension | GSM 850 | GSM 900/E-GSM 900 | GSM 1800 | GSM 1900 |
|------------------------------|--|--------------------------------|------------------------------------|------------------------------------|
| Frequency range (MHz) | TX: 824 – 849 MHz RX: 869 – 894 MHz | TX: 880 – 915 RX: 925 – 960 | TX: 1710 – 1785 RX: 1805 – 1880 | TX: 1850 – 1910 RX: 1930 – 1990 |
| Channel spacing | 200 kHz | 200 kHz | 200 kHz | 200 kHz |
| Number of channels | 124 Carriers *8 (TDMA) | 174 Carriers *8 (TDMA) | 374 Carriers *8 (TDMA) | 299 Carriers *8 (TDMA) |
| Modulation | 8PSK/GMSK | 8PSK/GMSK | 8PSK/GMSK | 8PSK/GMSK |
| TX Phase Accuracy | < 5° RMS Phase error (burst) | < 5° RMS Phase error (burst) | < 5° RMS Phase error (burst) | < 5° RMS Phase error (burst) |
| Duplex spacing | 45 MHz | 45 MHz | 95 MHz | 80 MHz |
| Frequency stability | +/- 0.1ppm | +/- 0.1ppm | +/- 0.1ppm | +/- 0.1ppm |
| Voltage operation (nominal) | 3.6 V | 3.6 V | 3.6 V | 3.6 V |
| Transmitter RF power output | 33 dBm Class 4 (2 W peak) | 33 dBm Class 4 (2 W peak) | 30 dBm Class 1 (1 W peak) | 30 dBm Class 1 (1 W peak) |
| Transmitter Output impedance | 50 ohm | 50 ohm | 50 ohm | 50 ohm |

| Dimension | GSM 850 | GSM 900/E-GSM 900 | GSM 1800 | GSM 1900 |
|--|---|---|-----------------------|-----------------------|
| Transmitter Spurious emission (according to specification) | < -36 dBm up to 1 GHz < -30 dBm over 1 GHz (according to spec.) | < -36 dBm up to 1 GHz < -30 dBm over 1 GHz | < - 30 dBm | < - 30 dBm |
| Receiver RF sensitivity | Better than – 102 dBm | Better than – 102 dBm | Better than – 102 dBm | Better than – 102 dBm |
| Receiver RX Bit error rate | < 2.4% | < 2.4% | < 2.4% | < 2.4% |

USSD technical data

| Feature | Support |
|--------------------|---|
| USSD support | GSM Phase 1/2 (Cross-phase compatibility) |
| Mode support -mode | UI-mode supported SAT initiated USSD supported |
| UI-mode details | <ul style="list-style-type: none"> It is possible to scroll the text up and down in USSD messages. It is possible to highlight embedded numbers and take actions accordingly. |

GPRS technical data

| Dimension | Support |
|--|--|
| Compatible GPRS and SMG specifications | Release 99 according to ETSI specification. |
| Data rates | Multislot class 10 supported (4+2) CS-1, CS-2, CS-3, CS-4 9,050 bps, 13,400 bps, 15,600 bps, 21,400 bps supported (network-dependent). |
| Medium Access Modes | Dynamic allocation |
| Support of Packet Control Channels (PBCCH/PCCCH) | Yes |
| Network operation mode | NOM I, II, III |
| Support of GPRS/CS combined procedures | Yes |
| Network control mode | NC0 and 2 |
| Support of access in 2 phases | Yes |

| Dimension | Support |
|--|---|
| Support of PRACH on 11 bits | Yes |
| Support of GPRS re-selection C31/C32 | Yes |
| Support of static and dynamic addressing | Yes |
| Support of power control Uplink and Downlink | Uplink = yes, Downlink is a network feature. |
| Support of ciphering algorithms | GEA1, GEA2 |
| Support of compression algorithms | Yes, V42bis and IP header compression. |
| Mode of operation | Class B and Class C modes of operation supported. |
| R Reference point | Physical layer: Support of RS232 PPP is supported as L2 layer in the R reference point Authentication algorithms PAP, CHAP supported |
| IP connectivity | PDP type IP is supported IP termination in mobile or TE (laptop, PDA) supported |
| PDP context | 10 PDP context descriptions stored in mobile PDP context description is edited via application in mobile, AT-command or via OTA Simultaneous PDP contexts are supported, maximum 2. |
| SIM | GPRS aware, as well as non-GPRS aware, SIM cards are supported. |
| AT commands supported | AT+CGDCONT - DEFINE PDP CONTEXT AT+CGEQREQ - Quality of Service Profile (REQUESTED) AT+CGEQMIN - Quality of Service Profile (Minimum Acceptable) AT+CGATT - PACKET DOMAIN SERVICE ATTACH OR DETACH AT+CGACT - PDP CONTEXT ACTIVATE OR DEACTIVATE AT+CGDATA - ENT |

SIM AT services supported

| Service | Mode | Support |
|----------------------|-----------------------|------------|
| CALL CONTROL BY SIM | | Yes |
| DATA DOWNLOAD TO SIM | Cell Broadcast SMS | Yes Yes |

| Service | Mode | Support |
|-----------------------|---|---------|
| DISPLAY TEXT | Text of up to 240 characters (120 UCS2 coded). | Yes |
| | bit 1: 0 = normal priority | Yes |
| | 1 = high priority | Yes |
| | bit 8: 0 = clear message after a delay | Yes |
| | 1 = wait for user to clear message | Yes |
| GET INKEY | General: The GET_INKEY requires that the user confirms his/her choice | Yes |
| | bit 1: 0 = digits (0-9, *, # and +) only | Yes |
| | 1 = alphabet set | Yes |
| | bit 2: 0 = SMS default alphabet | Yes |
| | 1 = UCS2 alphabet | Yes |
| | bit 3: 0 = character sets defined by bit 1 and bit 2 are enabled | Yes |
| | 1 = character sets defined by bit 1 and bit 2 are disabled and the Yes/No response is requested | Yes |
| GET INPUT | General: No. of hidden input characters | 252 |
| | bit 1: 0 = digits (0-9, *, # and +) only | Yes |
| | 1 = alphabet set | Yes |
| | bit 2: 0 = SMS default alphabet | Yes |
| | 1 = UCS2 alphabet | Yes |
| | bit 3: 0 = ME may echo user input on the display | Yes |
| | 1 = user input not to be revealed in any way (see note) | Yes |
| | bit 4: 0 = user input to be in unpacked format | Yes |
| | 1 = user input to be in SMS packed format | Yes |
| | bit 8: 0 = no help information available | Yes |
| | 1 = help information available | Yes |
| LANGUAGE NOTIFICATION | | Yes |
| LAUNCH BROWSER | | Yes |
| MORE TIME | | Yes |
| PLAY TONE | | Yes |
| POLLING OFF | | Yes |

| Service | Mode | Support |
|---------------------------|--|------------------------------------|
| POLL INTERVAL | | Yes |
| PROVIDE LOCAL INFORMATION | '00' = Location Information (MCC, MNC, LAC and Cell Identity) | Yes |
| | '01' = IMEI of the ME | Yes |
| | '02' = Network Measurement results | Yes |
| | '03' = Date, time and time zone (DTTinPLI) | Yes |
| | '04' - Language setting | Yes |
| | '05' - Timing setting | Yes |
| REFRESH | General: The reset option requests the user to wait while the phone restarts | Yes |
| | '00' =SIM Initialization and Full File Change Notification | Yes |
| | '01' = File Change Notification | Yes |
| | '02' = SIM Initialization and File Change Notification | Yes |
| | '03' = SIM Initialization | Yes |
| | '04' = SIM Reset | Yes |
| SELECT ITEM | | Yes |
| SEND DTMF | | Yes |
| SEND SHORT MESSAGE | bit 1: | 0 = packing not required |
| | | 1 = SMS packing by the ME required |
| SEND SS | | Yes |
| SEND USSD | | Yes |

| Service | Mode | Support |
|-----------------------|--|---------------------------------|
| SET UP CALL | General: Capability configuration | Yes |
| | Set-up speech call CallParty | No |
| | Subaddress DTMF support | Yes |
| | '00' = set up call, but only if not currently busy on another call | Yes |
| | '01' = set up call, but only if not currently busy on another call, with re-dial | Yes |
| | '02' = set up call, putting all other calls (if any) on hold | Yes |
| | '03' = set up call, putting all other calls (if any) on hold, with re-dial | Yes |
| SET UP EVENT LIST | '04' = set up call, disconnecting all other calls (if any) | Yes |
| | '05' = set up call, disconnecting all other calls (if any), with re-dial | Yes |
| | '00' = MT call | Yes |
| | '01' = Call connected | Yes |
| | '02' = Call disconnected | Yes |
| | '03' = Location status | Yes |
| | '04' = User activity | Yes |
| | '05' = Idle screen available | Yes |
| | '06' = Card reader status | Not Applicable |
| | '07' = Language selection | Yes |
| | '08' = Browser termination | Yes |
| | '09' = Data available | Yes |
| | '0A' = Channel status | Yes |
| SET UP IDLE MODE TEXT | | Yes, 1 row of text is supported |
| SET UP MENU | | Yes |
| TIMER MANAGEMENT | | Yes |
| OPEN CHANNEL | | Yes |
| CLOSE CHANNEL | | Yes |

| Service | Mode | Support |
|--------------------|------|---------|
| RECEIVE DATA | | Yes |
| SEND DATA | | Yes |
| GET CHANNEL STATUS | | Yes |

User Interaction with SIM AT

Display text

Text of up to 240 characters (120 UCS coded) is supported.

Text clearing times are 5-20 seconds and a 60-second time-out limit for the user to clear the text. 'Key' responses:

- 'Long Back' – Proactive session terminated by user.
 - 'Back' – Backward move in proactive session.
- Any other key clears the screen if the command is performed successfully.

Get inkey

Prompt for a one-character input. Pressing 'Ok' without entering a character gives warning message "Minimum 1 character". 'Key' responses:

- 'C' clears current character.
- 'Long Back' terminates the proactive session.
- 'Back' – Backward move in proactive session.
- 'OK' – Command performed successfully.

Get input

Prompt for character input. The phone will refuse to accept further input when maximum response length is exceeded. UI Maximum Response lengths:

- Digits Only – 160 characters.
- SMS default alphabet characters – 160 characters.
- Hidden Characters (digits only) – 20 characters.

'Key' responses:

- 'C' clears current character.

- 'Long Back' terminates the proactive session.
- 'Back' – Backward move in proactive session.
- 'OK' – Command performed successfully.

Select item

Scroll to highlight item for selection. 'Key' responses:

- Navigational key press down – Scroll down list.
- Navigational key press up – Scroll up list.
- Long 'Back' terminates proactive session.
- 'Back' – Backward move in proactive session.
- 'OK' – Command performed successfully.

Send short message

Default message "Sending message, please wait" can be replaced for the Alpha Identifier text, or suppressed completely if a null text is provided. Default responses are "MESSAGE FAILED" or "MESSAGE SENT". 'Key' responses:

- Long 'Back' or 'Back' ends the proactive session.

Set up call

If the Mobile Equipment (ME) is on a call when the command 'Set up Call', 'putting all other calls on hold' is sent, the user will see the text 'Setting up a call current call will be held'. If 'OK' is pressed the current call will be put on hold and the new call set up. If the ME is on a call when the command 'Set Up Call, disconnecting all other calls' is sent, the user will see the text 'Setting up a call current call will be disconnected'. If the 'OK' key is pressed the current call will be disconnected and the new call set up.

Set up menu

Incorporates a SIM Application Toolkit Menu Item into the ME's main menu structure.

If an Alpha Identifier is supplied in the Set Up Menu command, this is used as the SIM AT entry in the ME's main menu. If no alpha identifier is supplied and several items are found in the menu, a default title is used. If the SIM AT Menu Item is selected by pressing 'Select', all the items sent in the Set Up Menu command will be available for selection, in the same way as the Select Item command.

Walkman™ player

| File types | Formats | Extensions |
|---------------------------------|--|--|
| Audio | AAC, AAC+, Enhanced AAC+ MP3 (192 kbit/s for local playback) MP4 M4A 3GP (Audio encoded in AAC or AMR, able to play back AAC+) AMR WAV G-MIDI (level 1 with 24voices polyphony) SP-MIDI | .mp4 .mp3 .mp4 .m4a .3gp .amr .wav .mid .mid |
| Video (including audio part) | MP4 (video: MPEG4, audio: AAC, AAC+, enhanced AAC+ or AMR) 3GP (video: MPEG4 or H.263, audio: AAC or AMR) | .mp4 .3gp |
| Streaming transport | RTSP according to 3GPP™ | |
| Video coding | MPEG-4 Simple Visual Profile Level 0 H.263 Profile 0 Level 10 | |
| Audio coding | AAC, AAC+, enhanced AAC+, AMR, MPEG layer 3 | |
| Features | Automatic loop of songs in folder Automatic pause on telephone call. | |
| Ringtone file formats | MIDI (General MIDI 1, SP-MIDI) E-Melody I-Melody AMR-WB AMR-NB MP3 MP4 3GP M4A WAVE XMF | |

Radio with RDS

| | |
|--------|--|
| System | VHF/FM |
| Output | Portable handsfree External stereo speakers |

| | |
|---------------|---------------------------|
| System | VHF/FM |
| Save channels | Yes, 20 presets |
| Antenna | Stereo portable handsfree |

Imaging/Messaging

2.0 Megapixel camera

| | |
|----------------------------|--|
| Facts and figures | |
| Picture sizes (resolution) | 1600 x 1200 1280 x 960 640 x 480 |
| Color depth | 24 bit (8 bit per RGB channel), 16.7 million colors |
| Camera memory | Using phone memory, no memory dedicated to the camera only. |
| Digital zoom | 4x zoom |
| Picture light | No |
| Night mode | Yes |
| Self-timer | Yes |
| Effects | Negative/ Solarize/ Sepia/ Black&White/ Off |
| White balance | Auto/ Incandescent/ Fluorescent/ Daylight/ Cloudy |
| Picture quality | Choose between Normal and Fine |
| Shutter sound | 4 shutter sounds |
| Time and date | Add a time and date to a picture |
| Auto Focus | No |
| Shoot mode | Normal (no frame)/Panorama/Frames/Burst (4 pictures in rapid succession. Changes to 640x480 pixels automatically). |
| Video recorder | |
| Video sizes | 176 x 144 128 x 96 |
| Video shoot mode | High quality video(176 x 144)/Picture message (128 x 96) |
| Format | .3GP |
| Frames per second | 15 |

Pictures and animations

| | |
|-------------|--|
| Formats | JPEG, BMP, GIF (including animated), PNG, WBMP, and Scalable Vector Graphics (SVG) |
| Sharing via | Bluetooth™, MMS, email or Cable. |

Image decoders

| Decoder | Details | Size | Color depth | File format |
|---------|--|--------------------------------|-------------|--------------------|
| GIF | 87a/89a | Unlimited | | |
| JPEG | ISO/IEC JPEG Baseline DCT Progressive DCT Non-differential Huffman coding Symbol 'SOF2' | Unlimited | | JFIF v1.02 EXIF |
| BMP | The bitmap image format used by Windows®. | XRAM dependent, default is VGA | 24 bit | |
| WBMP | | Unlimited | | |
| PNG | | Unlimited | | |

Image encoders

| Decoder | Details | Size | Color depth | File format |
|---------|---|--------------------------------|-------------|-------------|
| GIF | 89a | | | |
| JPEG | ISO/IEC JPEG Baseline DCT Non-differential Huffman coding Symbol 'SOF0' | | | JFIF v1.02 |
| BMP | The bitmap image format used by Windows®. | XRAM dependent, default is VGA | 24 bit | |
| WBMP | | | | |

Supported character set

| Feature | Support |
|------------------------------|---|
| Decoding text (Incoming MMS) | <ul style="list-style-type: none"> • US-ASCII • ISO-8859-1 • ISO-8859-2 • UTF-7 • UTF-8 • UTF-16 • KOI8-R • Windows-1251 • ISO-40646-UCS-2 |
| Coding Text (Outgoing MMS) | UTF-8 |

Email client technical data

| Feature | Support |
|---------------------------|--|
| Bearer type GSM data (IP) | Yes, GPRS, HSCSD, ISDN, and analog |
| Character sets | <ul style="list-style-type: none"> • ISO: ISO-8859-1, ISO-8859-2, ISO-8859-5, ISO-8859-7, ISO-8859-9, ISO-8859-10 • Windows: Windows-1251, Windows-1252, Windows-1254, Windows-1255, Windows-1258 • US-ASCII • Unicode: UTF-7, UTF-8, UTF-16 • Japanese: Shift_JIS, ISO-2022-JP • Cyrillic: KOI8-R • Simplified Chinese: GB2312, GB18030 • Traditional Chinese: Big5 • Thai: TIS-60 |
| OTA provisioning solution | Yes |
| Protocols | POP3 and IMAP4 |
| Push email | IMAP Idle (extension of IMAP4Rev1), OMA Email Notification 1.0 and scheduled checking |
| Secure email | SSL/TLS, both port methods (POPS/IMAPS) and STARTTLS |
| Remote configuration | OMA Client Provisioning and Nokia Smart Messaging |
| HTML mail | Yes (tags removed) |
| Infinite images | Yes |
| Message management | Window of 50 latest messages Headers only or size limits |
| ESMTP | Yes |
| Background sending | Yes |

Short Messaging Service

| Feature | Support |
|--|---|
| SMS Center Number | It is possible to pre-load the SMS Center Number. |
| Pictures | It is possible to insert a picture or an icon into the text message. EMS compliant mobile phones will be able to see the picture correctly. |
| Capacity storage | Up to 1000 |
| Input methods | Predictive text input and multitap. |
| Reply to messages | It is possible to reply to received messages by SMS, phone call or email. |
| Message creation methods support | Predictive writing and multitap. |
| Copy, cut and paste words | No |
| Teaching of predictive words that are not in the predictive dictionary | Yes |
| Possibilities when creating a message: | |
| save a sent message in a "Sent items" folder | Yes |
| insert a line in the message | Yes |
| assign a validity period to the message | Yes |
| use pre-defined messages | Yes |
| Possibilities when receiving a message: | |
| reply to the sender | Yes (only to the sender, not to all or part of the message recipients). |
| forward the message | Yes |
| save the message on SIM | Yes |
| get delivery time and date | Yes |
| Possibilities of the previously sent message: | |
| delivery report of the message | Yes |
| forward the message | Yes |
| save the message on SIM | Yes |
| know the remaining capacity storage | Yes |
| Possibilities of the previously received message: | |
| reply to the sender | Yes (only to the sender, not to all or part of the message recipients). |
| save the message in the Inbox | Yes |

| Feature | Support |
|---|--------------------------------|
| forward the message | Yes |
| know the remaining capacity storage | Yes |
| Supported ways for replying to a received SMS: | |
| via SMS | Yes |
| via MMS | Yes |
| via Email | Yes |
| via phone call (set up a call to the number contained in the message body) | Yes |
| via WAP call (go to the WAP address contained in the message body) | Yes |
| via USSD session | No |
| SMS over GPRS | Yes |
| Possibility to offer the user the ability of sending an SMS to a list of recipients | Yes, using groups in Contacts. |
| Possibility to write an email address as a recipient address | Yes, if SMS type = email. |
| SMS storage | On the SIM and in the phone. |
| Nokia Picture Messaging | Yes |

Enhanced Messaging Service

| Feature | Support |
|--|---|
| Level of compliance supported by the phone regarding the specifications described in release 99. | Enhanced Messaging Service (EMS) according to the standard 3GPP™ TS 23.040 v4.3.0, with the addition of the ODI feature from 3GPP™ TS 23.040 v5.0.0. |
| Number of messages that the phone is able to handle to generate a concatenated message | 20 |
| Capacity storage | 1000 and the space left on the SIM card. |
| Outgoing messages | It is possible to... <ul style="list-style-type: none"> • see how many short messages an EMS message consists of before sending it. • choose whether to send the message or not after writing it. |

| Feature | Support |
|---|--|
| Incoming messages | <ul style="list-style-type: none"> • A signal is heard once all parts of the message have been received or when a time out occurs. • It is possible to re-use the content of an EMS message. Sounds, pictures, and animations can be inserted in a new message, if the object is not protected using ODI. |
| Concatenated messages | A receipt is received in the phone when all parts of a concatenated message have been delivered. |
| Insert objects | It is possible to add pictures, animations and sounds to an EMS message. |
| Sounds | Chimes high, chimes low, ding, tada, notify, drum, claps, fanfare, chords high, chords low. |
| I-melody | Yes, version 1.2. |
| Melodies | <p>It is possible to...</p> <ul style="list-style-type: none"> • send and receive melodies via EMS, if the melodies are not protected by copyright. • download melodies and commercial tunes from WAP/WAP portals. • create melodies on WAP/WAP portals. |
| WBMP | Yes |
| Picture sizes | 16x16 mm, 32 x32 mm, variable size in black and white. |
| Pictures | <p>It is possible to...</p> <ul style="list-style-type: none"> • edit pictures by using the phone keypad. • send and receive pictures via EMS, if the pictures are not protected by copyright. • create pictures on WAP/WAP portals. • download pictures from WAP/WAP portals. • receive pictures in enhanced messages originated by service providers. |
| Animations | <p>The phone supports the following animations: Angry, Crying, Flirty, Happy, Kiss, Sad, Tongue, Wow, Confused, Devil, Glasses, Indifferent, Laughter, Sceptical and Wink. Plus the other nine animations defined in 3GPP™ TS 23.040 v4.3.0.</p> <p>It is possible to...</p> <ul style="list-style-type: none"> • send and receive animations. |
| TP-PID field value given by the phone before sending an EMS message | 0x00 |

Multimedia Messaging Service

| Feature | Support |
|---|---|
| MMS/CSD parameters and MMS/GPRS parameters placement | MMS is bound to a WAP profile. A WAP profile is bound to a Data Account. A Data Account contains either CSD parameters or GPRS parameters. |
| Possibility to pre-configure the MMS parameters in factory | <ul style="list-style-type: none"> • MMS/CSD: Yes • MMS/GPRS: Yes |
| Possibility to configure the MMS parameters by OTA provisioning | <ul style="list-style-type: none"> • MMS/CSD: Yes • MMS/GPRS: Yes |
| Possibility for all the parameters from the parameters set to be OTA provisioned at the same time | <ul style="list-style-type: none"> • MMS/CSD: Yes • MMS/GPRS: Yes |
| Possibility for only one parameter from the parameters set to be OTA provisioned | <ul style="list-style-type: none"> • MMS/CSD: No • MMS/GPRS: No |
| OTA provisioning solution | OTA Settings Specification v7.1 © Ericsson and Nokia |
| Supplier indication of realized interoperability tests between its MMS User Agent and MMS Relay/Server from other suppliers | Yes |
| Support of a standard or a proprietary procedure for OTA provisioning of MMS parameters | Proprietary |
| Functionalities that the user is able to set during message composition: | <ul style="list-style-type: none"> • message subject • message priority • email recipient address • message Cc recipient(s) address(es) • delivery report request • read report request • MSISDN recipient address |
| From where can the user insert multimedia elements into multimedia messages: | <ul style="list-style-type: none"> • File Manager • directly from camera • Contacts • Calendar |
| Possibility for sent messages to be memorized into a folder in phone memory | Yes |
| Actions that the user can perform after message notification: | <ul style="list-style-type: none"> • Auto Download • Always Ask |
| Actions that the user can perform after message retrieval: | <ul style="list-style-type: none"> • reply to the sender of the message SMS/MMS • reply to the sender and to Cc people SMS/MMS • forward the message MMS • delete the message • save message into terminal • call the sender of a message |
| Multimedia codecs/formats supported for audio | AMR |

| Feature | Support |
|---|---|
| Multimedia codecs/formats supported for video | MPG4, 3GPP™, SDP |
| Multimedia codecs/formats supported for image | JPEG, GIF87, GIF89A, PNG, SVG, WBMP, BMP |
| Supported formats for message presentation: | <ul style="list-style-type: none"> • message body + attachments (email presentation) • SMIL version as described in OMA MMS IOP document version 1.2 |
| Maximum message size that can be handled by the phone for message | Content Class and Creation mode are applied. Maximum size is 500K. Maximum size is possible to customize. |
| Maximum number of objects supported in message | 30 |
| Maximum text size | 5,000 characters/text |
| MMS User Agent will report problems to user in case of: | <ul style="list-style-type: none"> • message not sent causes no user subscription to service, if included in ResponseText (please see WAP209) • message not sent causes required functionality not supported by MMS Relay/Server, if included in ResponseText (please see WAP209) • message not sent causes insufficient credit (in case of prepaid charging), if included in ResponseText (please see WAP209) |

Connectivity

Bluetooth™ technical data

| Dimension | Support |
|--------------------------------|--|
| Bluetooth capability statement | This phone is manufactured to meet Bluetooth Specification 2.0 |
| Bluetooth functions | Advanced Audio Distribution Profile (A2DP) Basic Imaging Profile Basic Printing Profile Dial-up Networking Profile File Transfer Profile Generic Access Profile Generic Object Exchange Profile Handsfree Profile Headset Profile Human Interface Device (HID) Profile JSR-82 Java API Object Push Profile Personal Area Network Profile Serial Port Profile Service Discovery Application Profile Synchronization Profile SyncML OBEX binding |
| Connectable devices | All products supporting Bluetooth™ spec. 1.1, or higher, and at least one of the profiles above. |
| Coverage area | Varies due to radio performance on remote device and the occurrence of obstacles. Up to 33 feet (10 meters). |
| Transmission power | 2mW (3 dBm) |
| Frequency band | 2.4 GHz - the unlicensed ISM band. |
| Power consumption | GSM host processor excluded: <ul style="list-style-type: none"> • Standby, Bluetooth On mode: <0.9mA • Voice mode: 24 mA • Data mode average: 25mA |
| Data transmission rate | Up to 2 Mbps from an application level. |

SyncML technical data

| Feature | Support for Sync ML |
|--------------------|--|
| SyncML compliance | The phone is fully SyncML 1.1 compliant (it passed SyncML Conformance testing). |
| Basic data formats | Contacts: vCard 2.1, Calendar: vCalendar 1.0, vTasks v1.0, vTodo v1.0, Notes: text/plain |

| Feature | Support for Sync ML |
|---|--|
| Possibility for operators to extend SyncML functionality. | No |
| Possibility to synchronize other phones using SyncML. | No |
| Transport method for SyncML messages. | HTTP, WSP (i.e. using a WAP connection), OBEX (USB, Bluetooth) |
| Synchronization application placement. | Inside the phone. |
| Possibility for the user to configure login parameters (e.g. username and password) to access the remote database. | Yes |
| Configuration parameters that can be entered/modified by the user. | Server URL, Server username, Server PWD, Paths to databases (Calendar, Contacts, Tasks and Notes) username and PWD for Databases, Databases to be synchronized (on/off), WAP Account, Synchronization interval and Remote initiation. Can be provisioned with Ericsson Nokia OTA Settings Specification v7.1 and OMA Client provisioning v1.1. |
| Mechanisms used by the phone to capture changes made by the end user (i.e. how does the SyncML client in the phone know which changes were made to the address book). | It uses a change log where it marks the contact as updated. |
| Ability to deal with multiple servers. | Yes |
| Ability to perform conflict resolution actions. | No |

Internet

Browser technical data

| Feature | Support in the browser |
|---------------------------|--|
| Back to previous page | Yes |
| Bearer type GPRS (IP) | Yes |
| Bearer type GSM Data (IP) | Yes, HSCSD, ISDN and analog. |
| Bookmarks | Yes, up to 100 named bookmarks for easy access to frequently visited pages. Folders and sorting supported. |

| Feature | Support in the browser |
|--------------------------|---|
| Bookmark Export/Import | Yes, can be sent and received using vBookmark format via Bluetooth™, SMS, MMS and email. |
| Cache | Yes (size 300 kB). |
| Character sets * | UTF-8 (Default), UTF-16, USASCII, Latin1, UCS2. *) When creating WML applications, it is recommended to always save the page contents as UTF-8, and that this is clearly indicated in the pages before publishing. This ensures that the contents of the application can be viewed, regardless of character sets used in gateways and the phone. All characters are not supported in all phones. The software version depends on which market the phone is associated to. Also, please note that the phone may not support input on a WAP Service which uses certain characters (languages), even if those characters are supported for browsing in the phone. |
| Clear cache | Yes |
| Color | Color screen. |
| Gateway | A WAP typically includes the following functions: A Protocol Gateway – the protocol gateway translates requests from the WAP protocol stack to the WWW protocol stack (HTTP and TCP/IP). Content Encoders and Decoders – the content encoders translate Web content into compact encoded formats to reduce the size and number of packets travelling over the wireless data network. |
| Home page | Yes, up to 10 different; one for each Internet profile. |
| HTML version for browser | XHTML, Mobile Profile 1.2, HTML 4.01, XHTML 1.1 including mobile phone. |
| Hyperlinks in Text | Yes, highlighted as blue underlined text. |
| Hyperlinks in Images | Yes, indicated by a frame |
| Image Animation | Yes |
| Image Formats | GIF (interlaced and non-interlaced) WBMP, no transparent layers, JPEG, PNG, BMP, SVG. |
| Network Settings | Up to 10 different settings available by selecting Internet profile (Internet, Banking, Gateway etc.). |
| OTA Support | Yes |
| PPP Authentication | PAP, CHAP supported. |
| Reload page | Yes |

| Feature | Support in the browser |
|---------------------|---|
| Security | TLS version 1, Client authentication SSL version 3, Client authentication WIM on SIM ICC X.509 certificate support, WAP Profile WMLScript signText WPKI OTA download of trusted certificates |
| Tables | Yes |
| User Agent Profiles | Yes, list of client characteristics - for example screen size. |
| WAP/WML WAP | WAP 2.0/WML 1.3 |
| WAP profiles | Dynamic - up to 10 WAP profiles, each with its own settings. |

Operator technical data

| Feature | Support for WAP | |
|---------------------------|---|---|
| Web Browser | | |
| Version | 2.0 baseline | |
| HTML | XHTML Mobile Profile | |
| Provisioning | | |
| Access NetFront 3.3 | <ul style="list-style-type: none">• HTML 4.01, XHTML 1.1 including mobile profile• CSS 1 & CSS 2 (partial)• ECMA Script 3rd edition/ equal to Java script 1.5• DOM level 1, level 2 and Dynamic HTML (partial)• Graphic formats: GIF, Animated GIF, JPEG, Progressive JPEG, PNG, MNG, BMP, WBMP | |
| Provisioning types | The Ericsson-Nokia OTA solution Over the Air Settings Specification, v7.1 © Ericsson and Nokia | OMA Client provisioning (v1.0) |
| Total Parameter sets | 10 (shared between the WAP provisioning types). < or = 10 (total number of WAP profiles). | |
| Parameter set list | <ul style="list-style-type: none">• name,• homepage and homepage title (1st bookmark element),• proxy/GW address,• bookmarks (remaining bookmark elements),• CSD phone number, | <ul style="list-style-type: none">• CSD data rate,• CSD dial type,• GPRS APN,• protocol authentication,• GW authentication,• secure connection on/off• CSD response timer,• GPRS QoS |
| Parameter sets include | WAP/CSD, WAP/GPRS (different sets). | |
| Factory pre-configuration | WAP/CSD (possibility to lock a setting), WAP/GPRS. | |
| OTA | WAP/CSD, WAP/GPRS configuration possible. | |
| Security mechanism | | |
| Bearer | The Ericsson-Nokia solution | OMA Client Provisioning |

| Feature | Support for WAP | |
|--------------------------------|--|---|
| OTA via SMS | Operator verification through a code that can be included in the OTA configuration data. This code is shown to the user who can choose to install or not. | Uses security mechanism (SEC) methods according to WAP-183-ProvCont-20010724-a (see www.openmobilealliance.org). |
| Interface | | |
| Bearer | The Ericsson-Nokia solution | OMA Client Provisioning |
| OTA via SMS | A question whether to install, with the code if available is asked. The user may have to choose whether to create a new WAP profile or to replace an existing WAP profile. | For NETWPIN the user is asked to accept to install received settings. For USERPIN, USERNETWPIN and USERPINMAC the user is subsequently asked to enter a PIN code that is a shared secret between the service provider and the user. |
| OTA via Cell Broadcast | - | The user is asked whether to accept the received settings or not. |
| Re-provisioning Interface | The Ericsson-Nokia solution | OMA Client Provisioning |
| OTA via SMS | Same interface as above. | If the settings previously installed were privileged or have higher priority, the settings might not be possible to install again unless the terminal is reset, otherwise as above. |
| OTA via Cell Broadcast | - | If the settings previously installed were privileged or have higher priority, the settings might not be possible to install again unless the terminal is reset, otherwise as above. |
| Carrier reset/provisioning | Yes, but not if the set is pre-configured in the factory and locked. | |
| SWIM | Not used for provisioning. The SWIM is only used for WAP security, digital signatures. | |
| SWIM certificate | Both client and trusted certificates can be used for digital signatures. | |
| Application provisioning | | |
| Preferred bearer customization | Yes | |
| Email provisioning | Yes, through Smart Messaging or OMA Client Provisioning. | |
| Other applications/features | Yes (MMS, SyncML, Wireless Village). | |
| Technologies | | |
| OMA Client provisioning | Yes, WAP provisioning document v1.0. | |

| Feature | Support for WAP |
|---|---|
| Openwave OTA | No |
| Other | Yes. The Ericsson-Nokia solution. OTA Settings Specification v7.1. |
| Provisioning bearer | SMS, Cell Broadcast |
| Parameter sets available | < or = 10 (total number of WAP profiles) |
| Parameter sets for OTA modification | < or = 10 (total number of WAP profiles) |
| PUSH | |
| Content types | |
| Service Indication (SI) | Yes |
| Service Loading (SL) | Yes |
| Cache Operation (CO) content type | Yes |
| Session Initiation Application (SIA) | Yes |
| Man Machine Interface | |
| SI/content retrieval postponing | Yes |
| SI menu structure accessibility | Messaging, Inbox |
| SL reception warning | The user can make a choice if a dialogue is wanted or not before loading the SL. Messaging/Settings/Push/Allow push msg/Always ask |
| SIA reception warning | Yes |
| Cache size limitations | The oldest push in the inbox will be discarded. |
| Number of push messages | Depending on the size of the push messages. Around 20 push messages with a size of 500 bytes can be stored. |
| Push de-activate | Yes (Messaging/Settings/Push/Allow push msg). |
| Dynamic push menu changes | No. There are no changes in the menus when activating/deactivating push. |
| Security | |
| Mechanisms for push | None |
| Trust with PPG | Sending a SIA is the most trustful. |
| WSP push sessions | The White List is supported. |
| Denial of service/spoofing | |
| User agent profile | |
| UA profile content sent at beginning of WSP session | No |

| Feature | Support for WAP |
|---|--|
| OA profile content size | |
| URL sent pointing to the UA profile at the beginning of WSP session | Yes |
| URL location | On the manufacturer WAP site. |
| WTAI | |
| WTA Make Call | Yes |
| WTA Send DTMF | Yes |
| WTA Add Phonebook | Yes |
| Other WTA/WTAI | No |
| DOWNLOAD | |
| WAP solutions | |
| SAR/WSP/HTTP GET solution to download content over WAP | Yes |
| Download Fun from Openwave | No |
| Other download content over WAP | Yes. Content download limited to 300 kB when using WTP protocol. No download limit when using HTTP protocol. |
| Features | |
| Download application/product memory check | Yes |
| Downloaded object solution | Yes. The user is asked if the content is to be saved. |
| UAP indication for downloading | Yes |
| Other features | Yes. Store, delete, forward, use, manage. |
| Object formats | All formats that are supported in the phone will be possible to download. |
| GRAPHICAL USER INTERFACE | |
| Man Machine Interface | |
| Selection keys | Yes |
| Separate/dedicated back or delete keys | Yes |
| Display backlight on when browsing | Yes |
| Predictive writing | Yes |
| “http://” string displayed automatically when entering URLs | Not displayed but the “http://” is added automatically to the URL. |
| Elements | |

| Feature | Support for WAP |
|--|--|
| Number of display lines for a WAP connection | Up to 8 rows (or 7 rows plus 1 title row), depending on the selected font size. Each row is 21 pixels in height (a title row is 28 pixels). |
| Pop-up menus | Yes, in XHTML. |
| Radio buttons | Yes, in XHTML. |
| Check boxes | Yes, in XHTML. |
| Buttons | Available as XHTML form controls. |

Sports Application

Facts and figures

| | |
|--|---|
| Running / jogging application – speed & distance with 90% accuracy in distance and speed | Yes |
| All day step count | Yes |
| Steps will be counted on a daily basis with automatic reset at 00:00 | Yes |
| Display daily progress on standby screen | Yes |
| Calories counter | Yes |
| Pocket train application | Graph results Medal rewards Sports trivia |

Java™

| Feature | Functionalities |
|-------------------------------|--|
| Java 2, Micro Edition (J2ME™) | <ul style="list-style-type: none"> • CLDC 1.1 (JSR 139) • MIDP 2.0 (JSR 118) • Wireless Messaging API (JSR 120/205) • Mobile Media API (JSR 135) • Java™ Technology for the Wireless Industry (JSR 185) • Java™ API for Bluetooth™ (JSR 82) • PDA Optional Packages for J2ME™ Platform (JSR 75) • Web Services (JSR 172) |

| Feature | Functionalities |
|----------|---|
| Java 3D™ | <ul style="list-style-type: none">• Mascot Capsule Micro3D Version 3• Mobile 3D Graphics API for J2ME™ (JSR 184) |

Abbreviations

3GPP™

3rd Generation Partnership Project

AAC

Advanced Audio Coding

AMR

Adaptive Multi Rate.
Audio format for speech sounds.

API

Application Programming Interface

ARPU

Average Revenue Per User

CS

Circuit Switched

CSD

Circuit Switched Data

CSS

Cascading Style Sheet

DRM

Digital Rights Management; controlling copying and distribution of contents, with respect to intellectual property rights.

DTMF or Touch Tone

Dual Tone Multi-Frequency signal – codes sent as tone signals. Used for telephone banking, accessing an answering machine, etc.

EDGE

Enhanced Data rates for Global Evolution.

eAAC+

Enhanced Advanced Audio Coder, formerly known as Enhanced Mpeg-4 AAC

e-GSM

Extended GSM. New frequencies specified by the European Radio Communications Committee (ERC) for GSM use when additional spectrum is needed (Network-dependent). It allows operators to transmit and receive just outside GSM's core 900 frequency band. This extension gives increased network capability.

EFR

Enhanced Full Rate, speech coding.

EMS

Enhanced Messaging Service. Allows the user to add simple pixel pictures and animations, sounds and melodies to a text message. The EMS 3GPP™ standard also includes text formatting.

ETSI

European Telecommunications Standards Institute.

FM

Frequency Modulation of the (radio) carrier wave.

FR

Full Rate, speech coding.

GIF

Graphics Interchange Format

GPRS

General Packet Radio Services

GSM

Global System for Mobile Communications. GSM is the world's most widely-used digital mobile phone system, now operating in over 100 countries around the world, particularly in Europe and Asia-Pacific.

The GSM system family includes GSM 850, GSM 900, GSM 1800 and GSM 1900. There are different phases of roll-out for the GSM system and GSM phones are either phase 1 or phase 2 compliant.

HR

Half Rate, speech coding.

HSCSD

High Speed Circuit Switched Data

HTML

HyperText Markup Language

HTTP

HyperText Transfer Protocol

JPEG

Joint photographer expert group

LED

Light Emitting Diode

MIDI

Musical Instrument Digital Interface

ME

Mobile Equipment

MIME

Multipurpose Internet Mail Extensions.

MMI

Man-Machine Interface. See UI.

MP3

Short for "MPEG-1 layer 3", an effective audio coding scheme.

MPEG4/MPG4

MPEG-4 extends the earlier MPEG-1 and MPEG-2 algorithms with synthesis of speech and video, fractal compression, computer visualisation and artificial intelligence-based image processing techniques.

MS

Mobile Station

MT

Mobile Termination

ODI

Object Distribution Indicator

OMA

Open Mobile Alliance

OTA

Over-the Air Configuration. To provide settings for the phone by way of sending an SMS message over the network to the phone. This reduces the need for the user to configure the phone manually.

PDA

Personal Digital Assistant

PDP

Packet Data Protocol

PIM

Personal Information Management

PNG

Portable Network Graphic

Quad-Band

GSM 850/900/1800/1900.

QVGA

Quarter Video Graphics Array

RTSP

Real Time Streaming Protocol session control.

SI

Service Indication

SL

Service Loading.

SIM card

Subscriber Identity Module card – a card that must be inserted in any GSM-based mobile phone. It contains subscriber details, security information and memory for a personal directory of numbers. The card can be a small plug-in type or credit card-sized, but both types have the same functions. The phone uses the small plug-in card.

SMS

Short Messaging Service. Allows messages of up to 160 characters to be sent and received via the network operator's message center to a mobile phone.

SP-MIDI

SP-MIDI stands for Scalable Polyphony MIDI.

SS

Supplementary Services

SSL

Secure Socket Layer

TLS

Transport Layer Security

UI

User interface

URL

Uniform Resource Locator.
The global address of documents and other resources on the World Wide Web.

USSD

Unstructured Supplementary Services Data

vCard

vCard automates the exchange of personal information typically found on a traditional business card, for use in applications such as Internet mail, voice mail, Web browsers, telephony applications, call centers, conferences, PIMs /PDAs, pagers, fax, office equipment, and smart cards. vCard is specified by IETF.

VGA

Video Graphics Array

VHF

Very high frequency. A band of radio frequencies falling between 30 and 300 MegaHertz.

WAP

Wireless Application Protocol. Handheld devices, low bandwidth, binary coded, a deck/card metaphor to specify a service. A card is typically a unit of interaction with the user, that is, either presentation of information or request for information from the user. A collection of cards is called a deck, which usually constitutes a service.

WAP Application

A collection of WML cards, with the new context attribute set in the entry card.

WAP service

A WML application residing on a web site.

WAV

WAV or WAVE (Windows Media Audio) is a Microsoft and IBM audio file format standard for storing audio on PCs.

WBMP

Wireless BitMap.

A graphic format optimized for mobile computing devices.

WWW

World Wide Web

XHTML

Extensible HyperText Markup Language

Related information

Documents

- Sony Ericsson User Guide
- Sony Ericsson FAQ
- AT Command Reference Manual
- WAP 2.0 Specifications

Links

- www.SonyEricsson.com/
- www.sonyericsson.com/support
- www.etsi.fr
- www.wapforum.org
- www.imc.org/pdi/
- www.syncml.org
- www.w3.org/TR/xhtml1-basic/
- www.java.sun.com

Trademarks and acknowledgements

The Bluetooth™ word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Sony Ericsson is under license.

The marble logo and Style-Up™ are trademarks of Sony Ericsson Mobile Communications AB.

Walkman™ is a trademarks or registered trademarks of Sony Corporation.

Memory Stick™ and Memory Stick Micro™ and M2™ are trademarks or registered trademarks of Sony Corporation.

QuickShare™, PlayNow™, VideoDJ™, MusicDJ™ and PhotoDJ™ are trademarks or registered trademarks of Sony Ericsson Mobile Communications AB.

XHTML™ is a registered trademark of the W3C.

Apple and Mac are trademarks of Apple Computer, Inc.

Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Contains Macromedia® Flash™ technology by Macromedia, Inc. Copyright 9C) 1995-2003 Macromedia, Inc. All rights reserved. Macromedia, Flash, Macromedia Flash and Macromedia Flash Lite are trademarks or registered trademarks of Macromedia, Inc. in the United States and other countries.

3GPP™ is a trademark of ETSI in France and other jurisdictions.

TrackID™ is powered by Gracenote Mobile MusicID™. Gracenote and Gracenote Mobile MusicID are trademarks of Gracenote, Inc. TrackID is a trademark or a registered trademark of Sony Ericsson Mobile Communications AB.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. End-user license agreement for Sun Java™ J2ME™.

1. Restrictions: Software is confidential copyrighted information of Sun and title to all copies is retained by Sun and/or its licensors. Customer shall not modify, decompile, disassemble, decrypt, extract, or otherwise reverse engineer Software. Software may not be leased, assigned, or sub licensed, in whole or in part.

2. Export Regulations: Software including technical data, is subject to U.S. export control laws, including the U.S. Export Administration Act and its associated regulations, and may be subject to export or import regulations in other countries. Customer agrees to comply strictly with all such regulations and acknowledges that it has the responsibility to obtain licenses to export, re-export, or import Software. Software may not be downloaded, or otherwise exported or re-exported (i) into, or to a national or resident of, Cuba, Iraq, Iran, North Korea, Libya, Sudan, Syria (as such listing may be revised from time to time) or any country to which the U.S. has embargoed goods; or (ii) to anyone on the U.S. Treasury Department's list of Specially Designated Nations or the U.S. Commerce Department's Table of Denial Orders.

3. Restricted Rights: Use, duplication or disclosure by the United States government is subject to the restrictions as set forth in the Rights in Technical Data and Computer Software Clauses in DFARS 252.227-7013(c) (1) and FAR 52.227-19(c) (2) as applicable.

All other trademarks and copyrights are the property of their respective owners.